

# MARKCOM MARK-1H



## The Markcom MARK-1H printer

is a mobile printer designed to be small and lightweight (400gr) and easy to use, with a durable lithium battery.

## Simple operation & Smarter

The embedded linux intelligent operating system provides a professional and user-friendly user interface.

5.0 Inch color industrial grade Touch-Screen experience better

WYSIWYG editing function is easy to operate.

ONE-TOUCH change the print density

A powerful algorithm for ink drop consumption is embedded to instantly calculate the cost of printing for customers.

## Built-in reliability

It Adopts American TI Company AM3358 industrial grade CPU and Xilinx Spant6 grade FPGA. It is more stable and reliable in industrial applications in various working conditions.

The print engine uses TIJ's dedicated ASIC chip to perfectly match HP's original and licensed inks.

Professional ink cartridge preheating algorithm ensures optimum print quality in a variety of high and low temperature environments.

## Practical - QR code

Powerful variable QR function to meet customer's various QR code application requirements.

Efficient and flexible variable database capabilities to meet a variety of traceability applications.

## Anti-interference Body

Body with plastic material that is not easily broken and lightweight

## Multiple Languages

Support 20 multi-Languages and keypad.

## Water Based Cartridge

Save Printing Cost

Up to **40%**



**MARKCOM®**





## MARK-1H SPECIFICATIONS

<b>Panel Control</b>	5" color touch screen
<b>User Interface</b>	Simple - user friendly UI
<b>Operating System</b>	Embedded Linux operating system
<b>Hardware</b>	American TI AM3358 Industrial-grade CPU/USA Xilinx Spant6 industrial-grade FPGA/TIJ dedicated ASIC chip
<b>Communication Interface</b>	USB/RJ45 to RS232
<b>External Interface</b>	Photocell (Included) Optional: -Encoder/reverse inverting control
<b>Print Engine</b>	TIJ Technology
<b>Message Store Capacity</b>	Up to 1000
<b>Multi-Laguanges</b>	English, Chinese, Arabic, Japanes, Korean, Thai, Vietnamese, French, German, Finnish, Italian, Norwegian, Portuquese, Spanish, Russian, Danish
<b>Indicator</b>	Display alarm indicator
<b>Print Resolution</b>	Resolution up to 600 x 600 DPI (vertical: 100DPI, 150DPI, 300DPI, 600DPI, lanscape: 30-600DPI precision adjustment)
<b>Print Density</b>	1 to 6 one-touch density
<b>Print Speed</b>	406m/90DPI, 304m120DPI, 240m/150DPI, 120m/300DPI, 60m/600DPI (multi-group variable data ultra-high speed response printing)
<b>Print Distance</b>	2 ~ 4 mm
<b>Print Height</b>	12,7mm (0,5") Variable adjustable font size and lines
<b>Print Capability</b>	Alpha numeric, date, time, month code, week code, alpha hours, counter, logos
<b>Barcodes</b>	QR Code, Data Matrix, EAN8, EAN12, Code128, Code39, UPCA, UPCE
<b>Nozzle Type</b>	Thermally foamable head TIJ2.5
<b>Ink Various</b>	Water-based, Solvent-based
<b>Catridge Chip</b>	Non-contact RFID, automatic identification and recording ink
<b>Electric Requirements</b>	Power adaper 100-240V AC input, 12V 3A DC output
<b>Working Environment</b>	Temperature of 0-45°C / humidity of 30-70% Rh
<b>Weight</b>	400gr
<b>Dimensions</b>	138(L) x 87 (W) x 36 (H) mm
<b>Orientation</b>	Side (Horizontal) - Downside

Distributed by:



**MARKCOM®**

